



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G1066Z 24" 5 HP VARIABLE-SPEED DRUM SANDER

Product Dimensions:

Weight..... 435 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 50 x 37 x 44-1/2 in.
Footprint (Length x Width)..... 34-1/2 x 24 in.

Shipping Dimensions:

Type..... Cardboard Box on Metal Skids
Content..... Machine
Weight..... 484 lbs.
Length x Width x Height..... 41 x 38 x 43 in.
Must Ship Upright..... Yes

Electrical:

Power Requirement..... 220V, Single-Phase, 60 Hz
Full-Load Current Rating..... 27A
Minimum Circuit Size..... 30A
Connection Type..... Cord & Plug
Power Cord Included..... Yes
Power Cord Length..... 6 ft.
Power Cord Gauge..... 12 AWG
Plug Included..... No
Recommended Plug Type..... L6-30
Switch Type..... Control Panel w/Magnetic Switch Protection

Motors:

Main

Horsepower..... 5 HP
Phase..... Single-Phase
Amps..... 25A
Speed..... 3450 RPM
Type..... TEFC Capacitor-Start Induction
Power Transfer Belt Drive
Bearings..... Sealed & Permanently Lubricated
Centrifugal Switch/Contacts Type..... External

Conveyor

Horsepower..... 1/3 HP
Phase..... Single-Phase
Amps..... 2A
Speed..... 60 RPM
Type..... Universal
Power Transfer Chain Drive
Bearings..... Sealed & Permanently Lubricated

Main Specifications:

Operation Information

Number of Sanding Heads.....	2
Maximum Board Width.....	23-1/2 in.
Minimum Board Width.....	2 in.
Maximum Board Thickness.....	4 in.
Minimum Board Thickness.....	1/8 in.
Minimum Board Length.....	9 in.
Sandpaper Speed.....	2300 FPM
Conveyor Feed Rate.....	0 – 20 FPM
Sandpaper Length.....	181-1/2 in.
Sandpaper Width.....	3 in.

Drum Information

Infeed Sanding Drum Type.....	Aluminum
Infeed Sanding Drum Size.....	6 in.
Outfeed Sanding Drum Type.....	Aluminum
Outfeed Sanding Drum Size.....	6 in.

Construction

Conveyor Belt.....	Rubber
Body.....	Steel
Paint Type/Finish.....	Powder Coated

Other Related Information

Floor To Table Height.....	33 in.
Sanding Belt Tension.....	Hook & Loop
Number of Pressure Rollers.....	3
Pressure Roller Type.....	Rubber
Pressure Roller Size.....	1-5/8 in.
Conveyor Belt Length.....	74 in.
Conveyor Belt Width.....	24 in.
Belt Roller Size.....	1-7/8 in.
Number of Dust Ports.....	2
Dust Port Size.....	4 in.
Mobile Base.....	D2058A, D2246A

Other Specifications:

Country of Origin	Taiwan
Warranty	1 Year
Approximate Assembly & Setup Time	30 Minutes
Serial Number Location	ID Label
ISO 9001 Factory	Yes

Features:

Hook & Loop Sanding Belt Tension/Sandpaper
Industrial-Duty Rubber Conveyor Belt
Two 4" Dust Ports
Variable Speed Conveyor
V-Belt Main Motor; Chain Drive Conveyor Motor
Dual 6" Aluminum Sanding Drums
Green Powder Coat Finish
Computer-Balanced Drums
Four-Leadscrew Table Lifting and Lowering System
Easy Access Control Panel with Amp Load Meter
External Micro-Adjustment on Outfeed Drum